*Manufacturers and suppliers of Specialised Landscaping & Turfcare Machinery*

**MUMBY Power Rotor Rake Tractor Mounted**

The Mumby tractor mounted Power Rotor Rakes are the ideal finishing tool to accurately level and rake off cultivated areas i.e., sports pitches - golf fairways - turf fields - amenity areas etc.
The rotating tine rotor augers unwanted stones and debris to the side via the hydraulic bi-angling of the rotor frame – known as windrowing – leaving a clean raked surface approaching a hand rake finish. Ideal for seeding and turfing preparation works, the long life welded high quality rotor teeth are maintenance free, making the stone rake a contractor's tool. Manufactured in a range of sizes for tractors 35-100hp.

**FEATURES:**

- Long life Rotor teeth made from high grade hardox steel – maintenance free
- Hydraulic bi-angling rotor frame
- Accurate depth control rear castor wheels
- Optional rake tine bar
- Heavy duty transmission with overload protection
- Interchangeable rotor system – optional carbide power box rotor or rotary brush
- Models available 180cm - 210cm - 240cm

Rotor Teeth – Hardox Steel

Hydraulic angling

Spring Tine Rotor optional

Standard build

**WORKING PRINCIPLE**

The Mumby Power rakes are all equipped with a special tine rotor which contra rotates and by hydraulic angling the rotor frame, unwanted stones and debris (down to 20mm in size) can be windrowed to the side and by continuing to move the ridge of material over on the following passes, large areas can be raked off – An optional rake tine bar increases productivity by pre-raking and a very accurate rake tine depth can be achieved by the adjustable rear castor wheels – ideal when working on high quality sports pitches for final grooming of the surface prior to seeding.

**SPECIFICATIONS**

| **Model** | **MPRR1800** | **MPRR2100** | **MPRR2400** | **MPRR3000** |
|---|---|---|---|---|
| Working rotor width | 180cm (71") | 210cm (83") | 240cm (95") | 300cm (118") |
| Rotor Teeth | Hardox | | | |
| Castor wheels/tyres | 24-13.00 x 12 | | | |
| Hydraulic angling | Standard | | | |
| Overload protection | Multi Plate adjustable friction clutch | | | |
| PTO Drive | 540rpm | | | |
| Tractor hitch | CAT 1 | CAT 1 & 2 | CAT 1 & 2 | |
| Tractor hp requirement | 30-60hp | 45-90hp | 50-100hp | |
| Dimensions | 200cm wide<br>145cm long<br>120cm high | 238cm wide<br>145cm long<br>120cm high | 270cm wide<br>210cm long<br>130cm high | 330cm wide<br>210cm long<br>130cm high |
| Weight kg | 565kg | 710kg | 1150kg | 1260kg |
| Commodity code | 8432 2910 | | | |
| Country of origin | United Kingdom | | | |